The Choice of Architects



C-Mine - Genk, Belgiun



ISO 9001 & ISO 14001 Certified

ТорСег

Sustainability & Environmental Statement

TopCer has long been committed to environmental friendly operations in the conception, manufacturing and trading of Unglazed Porcelain wall and floor tiles. TopCer ensures sustainability along production processes in accordance with standards and legal requirements, and simultaneously making sure that we meet client's needs and expectations.

Environmental awareness is present throughout all TopCer products lifecycle (please see our Environmental Product Declaration at our website www.topcer.com/general_data.php) namely:

- Best practices adoption of environmental management for continuous improvement and pollution prevention;
- Assuring that all raw materials used in the production process come from environmental conscious suppliers, preferably from suppliers with environmental certification;
- Committing ourselves to reduce energy consumption in all stages of our product life cycle;
- Ensuring that the sludge from water waste treatment and crushed porcelain pieces generated in our manufacturing process are re-used by a licensed waste operator in the production of structural ceramics as these residues due to the technical characteristics of Unglazed Porcelain Tiles cannot be re-integrated in production process;
- Encouraging the recycling of other types of waste in the main areas where they are produced, by disposal bins with appropriate labeling, in order to support and perform the separation of several types of plastic, cardboard and paper, paper and plastic cups, wood, etc. Assuring that the recycling of each type of waste occurs through licensed organizations specialized in respective fields.

TopCer Environmental Management System is certified by ISO 14001 as well as TopCer Quality Management System by ISO 9001.







TopCer

Founded in 1991, TopCer is an established worldwide brand, well known by the quality of their unique and innovative products.

TopCer is specialised in the manufacturing of Unglazed Porcelain Tiles in small modular sizes [10x10, 7.5x15, 15x15, 10x30 and 30x30] in various textures and shapes, complemented by a considerable line of matching trim pieces [49], all available in 30 colours.

The continuous research of traditional sizes, components and patterns used in the last two centuries, led Topcer to develop the collections "Victorian Designs and Borders" and "Contemporaneous Series", which offer traditional and modern innovative designs, back mesh mounted in modular sheets. These made possible in some markets to develop specific niches for their use in Palaces, Museums, Hotels, Restaurants and Pubs, Cruise Ships, private homes, restoration of old floors, etc.

TopCer tiles, due to their high breaking strengh, resistance to wear frost and non-slipping properties, are mostly used in all type of highly demanding areas.



Carlos R. Miguel Managing Director, TopCer















Colour Program



Colour's accuracy is limited by the print of this catalogue.



Stock Availability

(standard thickness 8 - 8.5 mm)

					RC	DD	RT	SS						RT
				10x10										
			SIZES											
OFFICE	001 01 10		S	45.45	2000	Sman	45.45	45.45	007	1.15.4	75.45			
SERIES	COLOUR 01	S Beige		15x15	15x15	15x15	15x15	15x15	OCT	HEX	7.5x15	10x30	30x30	30x30
	02	Speckled Grey		•	•	•	•	•	0	0	0	0	0	0
	03	Yellow		•	•	•	•	•	•	•	•	•	•	
	05	Old Rose		•	•	•	•	•	•	•	0	0	0	0
Series 1	06	Light Grey (Brown	1.1	•	•	•	•	•	•	•	•	•	•	•
	08	Granite Rose	,	•	•	•	•	•	0	0	0	0	0	0
	09	Granite Grey		•	•	•	•	•	0	0	0	0	0	0
	17	Speckled Brown		•	•	•	•	•	0	0	•	•	•	•
	1322													
Series 2	10	Granite Burgundy		•	•	•	•	•	0	0	0	0	0	0
CONGOL	24	Speckled Black/V	Vhite	•	•	•	•	•	0	0	0	•	•	•
	07	Light Grey (Blue)		•	•	•	•	•	•	•	•	•	•	0
	12 14	Granite Blue Black		•	•	•	•	•	•	•	•	•	•	•
	16	White		•	•	•	•	•	•	•	•	•	•	•
	19	Pink		•	•	•	•	•	•	•	•	•	•	0
Series 3	20	Brick-red		•	•	•	•	•	•	•	•	•	•	•
	21	Ochre Yellow		•	•	•	•	•	•	•	•	•	•	•
	22	Granite Green		•	•	•	•	•	0	0	0	0	0	0
	26	Speckled White		•	•	•	•	•	0	0	0	•	•	•
	28	Light Green		•	•	•	•	•	•	•	0	•	•	0
	30	Dark Grey		•	•	•	•	•	•	•	•	•	•	•
	04	Caramel		•	•	•	•	•	•	•	•	•	•	•
	13	Turquoise		•	•	•	•	•	•	•	•	•	•	0
Series 4	15	Medium Grey		•	•	•	•	•	•	•	•	•	•	•
	27	Light Blue		•	•	•	•	•	•	0	0	0	0	0
	29	Coffee Brown		•	•	•	•	•	•	•	•	•	•	•
	11	Blue (Cobalt)		•	•	•	•	•	•	•	•	•	•	•
	18	Dark Green		•	•	•	•	•	•	•	•	•	•	0
Series 5	23	Speckled Yellow		•	•	•	•	•	0	0	0	0	0	0
	25	Yellow (Lemon)		•	•	•	•	•	•	0	0	0	0	0
		-												

^[•] Means that we carry regular stocks. Orders are accepted for the minimum quantity of 1 carton.

If there is an enquiry for a small quantity of a specific colour/size/texture/thickness/shape that is not in the above list of regular stocks, please contact us to check if there is any material left from past productions.



⁽o) Means that colour is not available in the above sizes/textures/thickness but can become available at request subjected to a minimum order quantity of 500 m² (Customers must purchase any extra materials obtained in 1st quality for these customised orders, until the maximum of 10% of the ordered quantity).

Sizes & Shapes Smooth Textures

10 x 10 Loose



96x96x8

10 x 10 on mesh Sheet 30x30 (4 mm joint)



296x296x8

10 x 10 Octagon



10 x 10 Hexagon



100x115x8

10 x 10 Octagon with Dot 3x3 Sheet 30x30 (4 mm joint)



296x296x8

10 x 30

96x296x8





30 x 30



296x296x8.5



146x146x8 146x146x12 (*)



$Sizes \\ Textures Surfaces \\ _{M(cm) \, / \, W(mm)}$

RT



96x96x8.5

15 x 15



146x146x8.5

30 x 30

296x296x8.5

SS



96x96x8.5

15 x 15



146x146x8.5

RC



96x96x8.5

15 x 15



146x146x8.5

DD



96x96x8.5

15 x 15



146x146x8.5



96x96x8

15 x 15



146x146x8

30 x 30




[•] 146x146 at 12mm thickness and R surface is not available in stock. Orders are accepted for a minimum quantity of 500 sq.mt, subjected to the purchase of all material obtained in first quality till maximum of 10% of ordered quantity.



Trim Pieces

(mm)





NOTE: Trim Pieces are intended to be used as finishing pieces, matching only with TOPCER field tiles



Modular Sizes

(4mm standard joints)





- 1 4"x12" 10x30 (96x296x8mm)
- 2 12"x12" 30x30 (296x296x8.5mm)
- 3 4"x4" 10x10 (96x96x8mm)
- 4 6"x6" 15x15 [146x146x8mm]
- 5 3"x6" 7,5x15 (71x146x8mm)
- 6 6STP 29x146x8mm (MIAMI 30x30)

- 7 OCT 10x10 (96x96x8mm)
- 8 3D 29x29x8mm
- 9-6D-64x64x8mm
- 10 LZ 96x44x8mm
- 11 4TR 93x93x8mm
- 12 2TR 63x63x8mm 13 - 1TR — 45x45x8mm
- 14 TR1/2D 25x25x8mm
- 15 TR1/4D 20x20x8mm
- ,
- 16 5STP 21x137x8mm



Smooth

References



OPZ - Geel, Belgium



C-Mine - Genk, Belgium





WZC Menos - Genk, Belgium




St. Joseph Hospital - Berlin, Germany



Smooth





Telenet HQ - Mechelen, Belgium



Boulangerie Paul - Orly, France



Restaurant Bar, Sweden



Pivovar - Kaliningrad, Russia



Nando's Restaurant - Colchester, UK





Lido, Latvia



Fruehauf, Germany



Smooth



Fire brigade premises - Lisse, the Netherlands



Headquarters "Gasuni" - Groningen, the Netherlands




Cabrillo Boulevard - Santa Barbara, CA - USA



Woerden station, the Netherlands





Youth Hostel - Kortrijk, Belgium



Restaurant Vertigo - New York, USA



Comprehensive school - Ultrecht, the Netherlands



Private residence - Milan, Italy



Casa da Música - Oporto, Portugal



Gelredome Stadium - Arnhem, the Netherlands



Textured





Municipal Swimming Pool - Nordhausen, Germany





Swimming Pool Complex - Aulanko, Finland



Municipal Swimming Pool - Tammisaari, Finland



Kinsmead Pool, UK





Thermal Spa - Luso, Portugal



Caribia Hotel - Turku, Finland




Thermal Spa - Cabeço de Vide, Portugal






Mariebad Spa & Bad - Alands, Finland





Swimming Pool Complex - Ulvila, Finland







Swimming Pool Complex - Someron, Finland






Swimming Pool Complex - Someron, Finland







Burj Al Arab Helipad - Dubai, UAE



Centro Mariano - Fátima, Portugal



Packing

ESS		CARTO	ON / BOX			PALLET							
THICKNESS		Sizes	Pieces	Sq.mts	Sheets 30x30	Measurements (cm)	Cartons	Sq.mts	Gross Weight (kgs)				
		Mesh mounted											
		SMOOTH	126	1.26	14	120x100x78 H (B)	60	75.60	1320				
		DD	"	"	"	II .	"	=	1250				
		RC	"	"	II .	п	"	=	1280				
		RT	"	"	II .	п	"	=	1280				
		SS	"	"	"	п	"	=	1290				
		OCT with DOT	"	"	"	120x100x94 H (B)	54	68.04	1150				
	10x10 4"x4"	Loose											
	4 14	SMOOTH	100	1.00	-	120x80x65 H (A)	60	60	1040				
		OCT	"	"	-	ıı .	"	11	950				
	E	DD	"	"	_	120x80x75 H (A)	"	11	980				
E		RC	"	"	-	"	"	=	1010				
8 mm		RT	"	"	-	"	"	"	1010				
		SS	"	"	-	"	"	"	1020				
		HEXAGON	"	0.92	-	120x80x80 H (A)	54	49.68	910				
	7.5x15	Loose											
	3"x6"	SMOOTH	100	1.125	-	120x80x75 H (A)	60	67.50	1190				
		Loose											
		SMOOTH	50	1.125	_	120x80x75 H (A)	60	67.50	1200				
		DD	"	"	-	120x80x90 H (A)	65	73.125	1290				
		RC	"	"	_	II .	"	"	1340				
		RT	"	"	-	II .	"	=	1320				
	15x15	SS	"	"	-	II .	"	=	1340				
	6"x6"	Loose											
		SMOOTH	34	0.765	_	120x80x75 H (A)	60	45.9	1220				
8		DD	36	0.81	-	120x80x90 H (A)	65	52.65	1340				
2 mm		RC	"	"	-	"	"	=	1350				
-		RT	"	"	_	п	"	=	1380				
		SS	"	"	_	п	"	=	1390				
	10x30	Loose							•				
_	4"x12"	SMOOTH	34	1.02	-	120x80x75 H (A)	60	61.2	1070				
ШШ		Loose											
ω	30x30 12"x12"	SMOOTH	11	0.99	-	120x80x75 H (A)	60	59.40	1170				
	12 X 12"	RT	п	п	-	"	II .	11	1120				
		I		1		l							

			20 FEET C	TRUCK / CAMION				
			191	tons	21.5	tons	24 tons	
SS Sizes		Pallet	Sq.mts.	Pallet	Sq.mts.	Pallet	Sq.mts.	
		Mesh mounted						
		SMOOTH, DD, RC, RT, SS	14 (B)	1058.4	16 (B)	1209.6	18 (B)	1360.8
	10x10 4"x4"	Loose						
		SMOOTH	18 (A)	1080	21 (A)	1260	23 (A)	1380
		DD, RC, RT, SS	18 (A)	1080	21 (A)	1260	23 (A)	1380
ے	7.5x15 / 3"x6" 15x15 / 6"x6"	Loose						
Ē		SMOOTH	16 (A)	1080	18 (A)	1215	20 (A)	1350
ω	15x15 6"x6"	Loose						
		DD, RC, RT, SS	14 (A)	1023.75	16 (A)	1170	18 (A)	1316.25
	10x30 4"x12"	Loose						
		SMOOTH	18 (A)	1101.6	20 (A)	1224	22 (A)	1346.4
	30x30	Loose						
	12"x12"	SMOOTH, RT	16 (A)	950.4	18 (A)	1069.2	20 (A)	1188

Detailed packing of all TopCer products is available at www.topcer.com/general_data.php (detailed packing)

size 120x80 27 Kg

(A) EUR size 120x80 27 Kg (B) EUR 2 / EUR 3 size 120x100 30 Kg



Technical Data

Unglazed porcelain tiles — ISO 13006 and EN 14411 - Annex G - Group Bla									
SIZES:	M(=N)	10x10	10x30	7.5x15	15x15	30x30	DESIGNING .		
SIZES:	W	96x96x8	96x296x8	71x146x8	146x146x8	296x296x8.5	COMPONENTS ^{a)}		

a) Including 6STP (W29x146x8), 5STP (W21x137x8), 6D (W64x64x8), 3D	(W29x29x8), LZ	(W96x44x52x8), TR (W93x93x8	, W64x64x8, W45x45x8, W2	5x25x8 y W20x20x8)		
PHYSICAL PROPERTIES	TEST STANDARD	A 4 45	REQUIREMENT	rs	TOPCER VALUE		
DIMENSION AND SURFACE QUALITY:		Area≤ 49 cm or N < 7 cm	^{1*} 7 cm≤N<15 cm	N≥15 cm			
Length and width	ISO 10545-2	± 0,5mm	± 0,9mm	± 0,6% / ± 2,0mm	Conforms		
Thickness	ISO 10545-2	No testing	± 0,5mm	± 5,0% / ± 0,5mm	Conforms		
Straightness of sides	ISO 10545-2	No testing	± 0,75mm	± 0,5% / ± 1,5mm	Conforms		
Rectangularity	ISO 10545-2	No testing		± 0,5% / ± 2,0mm	Conforms		
Surface flatness, (curvature and warpage)	ISO 10545-2	No testing		± 0,5% / ± 2,0mm	Conforms		
Surface quality	ISO 10545-2		≥ 95%		Conforms		
PRODUCT QUALITY AND DURABILITY:	100 100 101				Comornio		
Water absorption	ISO 10545-3		≤ 0,5%		≤ 0,1%		
·	ISO 10545-4		≥ 1300 N		≥ 1800 N		
Breaking strength							
Modulus of rupture	ISO 10545-4		≥ 35 N/mm²		≥ 50 N/mm²		
Impact resistance	ISO 10545-5		Declared Value		No visible defects		
Resistance to deep abrasion (unglazed tiles)	ISO 10545-6		≤ 175 mm³		123 mm ³		
Coefficient of linear thermal expansion	ISO 10545-8		Declared Value		5,6 x 10 ⁻⁶ °C ⁻¹		
Thermal shock resistance	ISO 10545-9		No visible defects		Conforms		
Moisture expansion	ISO 10545-10		Declared Value		< 0,1 mm/m		
Frost resistance	ISO 10545-12		No visible defects		Conforms		
Resistance to chemicals	ISO 10545-13		No visible defects		Conforms		
Resistance to staining	ISO 10545-14		No permanent stain	ing	Conforms		
SLIP RESISTANCE: (For the designing com		or hetter than s		0			
(, , ,							
	Dynamic Coefficient of Fr		·)				
	ACTA ANGLA ACT A COAC	VALUES:	40.40.748.458	F			
	ASTM - ANSI A 137.1-2012 (INTERTEK - CA)	0.62	10x10 / 4"x4 Plain	,			
		0.65	10x10 / 4"x4 Riven	(HT) linish			
	AS 4586:2013 Apendix B (ATTAR - AU)	0.65	10x10 / 4"x4 Plain F	Finish (smooth)			
	-	_	,				
	Wet Pendulum Slip Resis	tance					
	AS 4586:2013 Apendix A	47	10x10 / 4"x4 Plain F	Finish (smooth)			
	(ATTAR - AU)		•				
	Pendulum	VALUES:					
	BS-7976-2	DRY W	DRY WET SIZES / SURFACE TEXTURE				
Areas with footwear		60 3	37 10x10 / 15x15 Plain finish (smooth)				
Al das with reserved		61 53 15x15 Riven (RT) finish					
	(CERAM - UK)	67 54 15x15 Square studs (SS) finish					
		81 7	81 70 15x15 Round studs (RC) finish				
		87 7	2 15x15 Diamond stud	s (DD) finish			
			ass SIZES / SURFACE				
			,				
				10x10, 15x15, 30x30 Plain finish (smooth) 30x30 Dies lined with spec. rubber (R) Plain finish			
				10x10 / 15x15 Dies lined with spec. rubber (R) Plain finish			
			,		Fidiri III IISTI		
			3 10x10 Riven (RT) finis				
	UNE-ENV 12633		B 15x15 Riven (RT) finis				
	(ITC - SPAIN)		· ·	10x10 Square studs (SS) finish 15x15 Square studs (SS) finish			
		48 3	3 15x15 Square studs				
		52 3	3 10x10 Round studs (RC) finish			
		56	3 15x15 Round studs (RC) finish			
		49	3 10x10 Diamond stud	s (DD) finish			
		59 3	3 15x15 Diamond stud	s (DD) finish			
	Ramp Test	VALUES:					
		6° ≤ R9 ≤	10° 30x30 Plain finish (sr	noothl			
		10° < R10 :	,	•	15x15 Plain finish (smooth)		
	DIN 51130	19° < R11 :	-	10x10 (also Hexagon and Octagon) / 10x30 / 15x15 Plain finish (smoo			
	(HS-KOBLENZ - DE)	15 11111		10x10 / 15x15 Square studs (SS) and in Round studs (RC) 30x30 Rubber (R), 30x30 Riven (RT)			
		27° R12 s		10x10 / 15x15 Riven (RT) and in Diamond studs (DD)			
		V5	· · · · · · · · · · · · · · · · · · ·				
F: 1	DIN 51130/BGR 181	V6		15x15 Square studs (SS) and Riven (RT) 10x10 Square studs (SS) and Riven (RT) 15x15 Round studs (RC)			
Displacement volume / Expulsion space	(HS-KOBLENZ - DE)	V0 V7	·	10x10 Square studs (SS) and Riven (RT), 15x15 Round studs (RC) 15x15 Diamond studs (DD)			
Exhaision shace	(1 10-NUDLEINZ - DEJ						
Annual with home for the	DIN E4007 (101/05: =: = = =	V8	10x10 Round studs (
Areas with bare-footed	DIN 51097 (HS-KOBLENZ - DE)	12°≤ A<1	•	•			
	(HS-KOBLENZ - DE)	18°≤ B<2			15x15 Plain finish (smooth)		
	(OEDANA LIIK)	30x30 Rubber (R), 30x30 Riven (RT)					
			-4 LUXIU / LDXID Plain	DOMESTI ISTO DOCTO			
	(CERAM - UK)	18°≤B<2			(DT) (C 1 / (CC)		
	(CERAM - UK) (CERAM - UK) (HS-KOBLENZ - DE)	C ≥ 24	15x15 Round studs (F	C)+Diamond studs (DD)+Riv	ven (RT)+Square studs (SS) D)+Riven (RT)+Square studs (S		



TopCer



Aerial view



Pressing



Lab control & testing



Firing



Selection



The Choice of Architects





www.topcer.com

EXPORT OFFICE:

Largo da Estação, 8 - 2º Fte - 2750-340 Cascais • Portugal Tel. +351 214 844 788/9 - Fax +351 214 841 091 Email: LX@topcer.com

FACTORY:

Rua do Monte Grande 10, Zona Industrial de Oiã - 3770-068 OIÃ • Portugal Tel. +351 234 722 395 - Fax +351 234 722 397 Email: av@topcer.com







Cabrillo Boulevard - Santa Barbara, CA - USA