

# Calacatta

design

**Giovanni Barbieri**





# Calacatta

La bellezza del marmo appena estratto. Rivestimenti dal bianco incantevole e delicate venature.

The beauty of the marble just extracted. Wall tiles of enchanting white and delicate grains.

Красота только что добытого мрамора. Облицовка чарующего белого с нежными прожилками.



# Calacatta

Pezzi unici che  
arredano la casa con  
infinite varianti e  
sfumature cangianti.

Unique pieces that  
decorate the house with  
endless variants and  
iridescent nuances.

Уникальные элементы, которые  
украсят ваш дом с помощью своих  
бесконечных вариантов рисунка и  
переливающихся оттенков.



# Calacatta

Varietà di formati e decorazioni  
per rivestimenti e pavimenti.

Lo stile ineguagliabile di Calacatta  
riveste gli spazi dell'eleganza  
tipica dei marmi più pregiati.

Range of sizes and decorations  
for walls and floors.

The incomparable style of Calacatta  
covers the spaces of elegance  
typical of the most precious marbles.

Разнообразие форматов и декоров  
для стен и полов. Несравнимый стиль Calacatta  
украшает интерьер с элегантностью, свойственной  
самому ценному мрамору.

CALACATTA



Calacatta 60x60 - 23,6"x23,6"  
Ambra Collection 60x60 - 23,6"x23,6"  
Bacchetta Cromo 1,5x90 - 0,6"x35,5"  
Tabula XL Noce 20x120 - 7,9"x47,2"



Calacatta 60x60 - 23,6"x23,6" - Ambra Collection 60x60 - 23,6"x23,6" - Bacchetta Cromo 1,5x90 - 0,6"x35,5"





Calacatta 7,5x30 - 2,9"x11,8"  
Ottagona 30x30 - 11,8"x11,8"  
Matita 1,5x30 - 0,6"x11,8"

# CALACATTA



Calacatta 7,5x30 - 2,9"x11,8" - Ottagona 30x30 - 11,8"x11,8" - Matita 1,5x30 - 0,6"x11,8"







Calacatta 60x60 - 23,6"x23,6" - 30x60 - 11,8"x23,6" - 30x30 - 11,8"x11,8" - 7,5x30 - 2,9"x11,8"  
Matita 1,5x30 - 0,6"x11,8" - Torello 3,5x30 - 1,4"x11,8" - Listello Mosaico 2x30 - 0,8"x11,8"





Calacatta 30x30 - 11,8"x11,8"  
7,5x30 - 2,9"x11,8"  
Esagona 32x37 - 12,6"x14,5"  
Matita 1,5x30 - 0,6"x11,8"  
Torello 3,5x30 - 1,4"x11,8"  
Ang. Torello 3,5x3,5 - 1,4"x1,4"  
Coprifilo 1,5x30 - 0,6"x11,8"


# Calacatta

DIGITAL  
TECHNOLOGY


GRES PORCELLANATO  
IMPASTO COLORATO



G2042A CALACATTA VI. LAPP. RETT. 67  
7,5x30 - 2,9"x11,8"



G2041A CALACATTA VI. LAPP. RETT. 64  
30x30 - 11,8"x11,8"



G20402 CALACATTA VI. 13  
MOSAICO 30x30 (tozz. 5x5) 11,8"x11,8"



G20413 CALACATTA VI. 17  
COPRIFILO  
1,5x30 - 0,6"x11,8"



G2077A CALACATTA VI. 67  
LAPP. RETT. 20x20 - 7,9"x7,9"



G2081A CALACATTA VI. LAPP. RETT. 20x60 - 7,9"x23,6" 47



G2037A CALACATTA VI. LAPP. RETT. 60x120 - 23,6"x47,2" 67



G2038A CALACATTA VI. LAPP. RETT. 30x60 - 11,8"x23,6" 64



G2039A CALACATTA VI. LAPP. RETT. 60x60 - 23,6"x23,6" 65




G20405 CALACATTA VI. BATTISCOPA 8x60 - 3,1"x23,6" 16

G20410 CALACATTA VI. 2  
CHIUSURA ESAGONA  
ORIZZONTALE  
4,8x4,2 - 1,9"x1,6"



G20403 CALACATTA VI. 37  
ESAGONA 32x37 - 12,6"x14,5"

G20431 CALACATTA VI. 2  
CHIUSURA ESAGONA  
VERTICALE  
3x9,5 - 1,2"x3,7"



G20404 CALACATTA VI. 34  
OTTAGONA 30x30 - 11,8"x11,8"

G20408 CALACATTA VI. MATTITA 12  
1,5x30 - 0,6"x11,8"


G20407 CALACATTA VI. TORELLO 21  
3,5x30 - 1,4"x11,8"

G20409 CALACATTA VI. LISTELLO 11  
MOSAICO 2x30 - 0,8"x11,8"

G20412 CALACATTA 26  
VI. ANG. TORELLO  
3,5x3,5 - 1,4"x1,4"



G20400 CALACATTA VI. 29  
MOSAICO 30x30 (tozz. 6x6) 11,8"x11,8"



G2040A CALACATTA VI. AMBRA RETT. 60x60 - 23,6"x23,6" 65

G30801 BACCHETTA ALLUMINIO 19  
1,5x90 - 0,6"x35,5"

G30802 BACCHETTA CROMO 19  
1,5x90 - 0,6"x35,5"

G30803 ANG. 6  
BACCHETTA ALLUMINIO  
1,5x1,5 - 0,6"x0,6"

G30804 ANG. 6  
BACCHETTA CROMO  
1,5x1,5 - 0,6"x0,6"




Calacatta 7,5x30 - 2,9"x11,8"



Formato Size cm Format cm Формат см	Pezzi/scatola Pieces/box Pièces/boîte Stück/Karton Изделий/коробку	Mq/scatola Sq.Mt./box Mq/boîte Qm/Karton M2/коробку	Kg/scatola Weight/box Poids/boîte Gewichte/Karton Kr/коробку	Scatole/pallet Box/pallet Boîte/pallet Karton/pallet Коробок/паллеты	Mq/pallet Sq.Mt./pallet Mq/pallet Qm/pallet M2/паллеты	Kg/pallet Weight/pallet Poids/pallet Gewichte/pallet Kr/паллеты	Spessore Thickness Epaisseur Stärke Толщина
60x120 Fondo	2	1,44	36	21	30,24	776	10
60x60 Fondo	3	1,08	25,3	40	43,2	1032	10
30x60 Fondo	6	1,08	25,3	40	43,2	1032	10
20x60 Fondo	9	1,08	22,46	48	51,84	1098,08	10
20x20 Fondo	25	1	21	60	60	1280	10
30x30 Fondo	13	1,17	27,4	40	46,8	1116	10
7,5x30 Fondo	26	0,585	12,90	60	35,1	794	10
60x60 Ambra Collection	3	1,08	25,3	40	43,2	1032	10
30x30 Mosaico (5x5)	11	-	18,15	-	-	-	-
30x30 Mosaico (6x6)	6	-	9,86	-	-	-	-
32x37 Esagona	10	-	14	-	-	-	-
30x30 Ottagona	11	-	14	-	-	-	-
2x30 Listello Mosaico	12	-	1,5	-	-	-	-
3,5x30 Torello	6	-	1,158	-	-	-	-
3,5x3,5 Ang. Torello	10	-	0,118	-	-	-	-
1,5x30 Matita	6	-	0,65	-	-	-	-
1,5x30 Coprifilo	8	-	0,27	-	-	-	-
8x60 Battiscopa	20	-	20	-	-	-	-

CARATTERISTICHE TECNICHE Technical Characteristics - Caracteristiques Techniques - Technische Eigenschaften CONFORME - ACCORDING TO - CONFORME - GEMÄß ANSI 137.1 Impervious porcelain tiles				GRES PORCELLANATO IMPASTO COLORATO
comunica VALLELUNGA	CARATTERISTICHE TECNICHE TECHNICAL CHARACTERISTICS CARACTERISTIQUES TECHNIQUES TECHNISCHE EIGENSCHAFTEN	METODO DI PROVA ASTM TEST METHOD ASTM METHODE D'ESSAI ASTM PRÜFMETHODE ASTM	REQUISITI PRESCRITTI Required Value Valeur Requise Vorgeschriebener Wert ANSI 137.1	VALORI Value/Valueur/Wert VALLELUNGA SMALTATO GLAZED GL
	<b>ASSORBIMENTO D'ACQUA</b> WATER ABSORPTION ABSORPTION D'EAU WASSERABSORPTION	EN-ISO 10545-3	0,5% (fully vitrified)	≤ 0,05
	<b>RESISTENZA ALLA ROTTURA</b> BREAKING MODULUS RÉSISTANCE À LA FLEXION BIEGEFESTIGKEIT	EN-ISO 10545-4	≥250 Pounds ≥113 Kg ≥1110 N	CONFORME Compliant
	<b>DUREZZA MOHS</b> MOHS HARDNESS DURETÉ MOHS HÄRTE MOHS	EN-ISO 101		MOHS 5
	<b>RESISTENZA ALL'ABRASIONE</b> ABRASION RESISTANCE RÉSISTANCE À L'ABRASION ABRASIONSWIDERSTÄNDIGKEIT	EN-ISO 10545-7	NON RICHIESTO Not required	METODO DI PROVA ISO 10545-7 PEI V
	<b>RESISTENZA AGLI SBALZI TERMICI</b> THERMAL SHOCK RESISTANCE RÉSISTANCE AUX CHOC THERMIQUES TEMPERATURWECHSELBESTÄNDIGKEIT	ASTM C484	RICHIESTO required	RESISTENTE Resistant
	<b>RESISTENZA ALL'ATTACCO CHIMICO</b> CHEMICAL RESISTANCE RÉSISTANCE CHIMIQUE CHEMISCHE BESTÄNDIGKEIT	EN-ISO 10545-13	NON RICHIESTO Not required	RESISTENTE Resistant
	<b>RESISTENZA AL GELO</b> FROST RESISTANCE RÉSISTANCE AU GEL FROSTBESTÄNDIGKEIT	EN-ISO 10545-12	NON RICHIESTO Not required	RESISTENTE Resistant
	<b>RESISTENZA ALLE MACCHIE</b> STAIN RESISTANCE RÉSISTANCE AUX TACHES FLECKENBESTÄNDIGKEIT	EN-ISO 10545-14	NON RICHIESTO Not required	RESISTENTE Resistant
	<b>COEFFICIENTE DI ATRITO DINAMICO</b> DYNAMIC FRICTIONS FROTTEMENT DYNAMIQUE DYNAMISCHE REIBUNG	BOT 3000 ANSI A 137.1	WET ≥ 0,42	CONFORME Compliant
	<b>SPESORE</b> THICKNESS ÉPAISSEUR STÄRKE	ASTM C485 Planarit Warpage	≤ 1,0% Sui lati/On sides ≤ 0,75% Sulle diagonali/On diagonals	CONFORME Compliant
		ASTM C499 Dimensioni Dimensions	≤ 3,0% Sulle dimensioni nominali Of nominal dimensions ≤ 1,5% Differenza nel lotto tra valori min. e max./Difference in batch between min. and major values	CONFORME Compliant
		ASTM C499 Spessore Thickness	≤ 0,040 inch Differenza nel lotto tra spessore min. e max. Difference in batch between min. and major thickness	CONFORME Compliant
		ASTM C502 Parallelismo dei lati Wedging	≤ 1,0 %	CONFORME Compliant





01036 NEPI (VT) Loc. Settevene Via dell'Industria n, 7 Tel. 0761 5291 - 4 linee - Fax. 0761 527156  
[www.vallelungacer.it](http://www.vallelungacer.it) - [www.vallelungaceramica.ru](http://www.vallelungaceramica.ru)