



FS Marrakech

Single fired floor tiles



FS MARRAKECH | FS MARRAKECH GREY FS OMEYA GREY, BLACK; WHITE


NEW



FS MARRAKECH Grey



FS MARRAKECH blue



6 patterns

45*45*1,05 cm | 17 3/4" * 17 3/4" * 7/16"

	NATURAL PRICE CODE BN14
GREY	21937
BLUE	21936

CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO | ANTI-SLIP CHARACTERISTICS

Ensayo Essay	Características Features	Resultado Result
DIN 51130	Ángulo crítico (Pies calzados) Critical angle (footwear)	R9
DIN 51097	Ángulo crítico (Pies descalzos) Critical angle (Wet loaded barefoot)	—
BS-7976-2	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	+36 Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	Class 1
ANSI A.1371:2012	Coefficiente de Fricción Dinámico Dynamic Coefficient of Friction	—
ISO 10545-7	Resistencia a la Abrasión Superficial/Resistance to Surface Abrasion	PEI 4

APLICACIONES | APPLICATIONS

Área Area	Revestimiento Wall	Pavimento Floor
Interior Internal	✓	✓
Exterior External	-	-
Comercial Commercial	-	-
Ducha Shower	-	-

CARACTERÍSTICAS TÉCNICAS | TECHNICAL CHARACTERISTICS

joint 15mm	versatile	matt
diferent shades	shade variation	various graphics

EMBALAJE | PACKING

Formato Sizes	Cajas Boxes			Pallet			Cont./20'		
	Piezas	m ² / sq.m	kg	Cajas	m ² / sq.m	kg	Tamaño cm aprox.	m ² / sq.m	m ² / sq.m
cm 45 * 45 * 1,95	5	1	23,14	66	66,83	1552,2	120 * 80 * 105	925,59	1033,22
inch 17 3/4 * 17 3/4 * 3/4	5	10,9	50,9	66	719,3	3414,9	47 1/7 * 31 1/2 * 41 5/16	9962,96	11121,44